

P4150

Single Ply Neoprene Coated Glass Fabric Ducting



Construction: Lightweight, very flexible ducting made with high tensile spring steel wire helix, covered with neoprene coated glass fabric with a single outer glass fibre cord.

Colour: Black with white cord.

Standard length: 4 metres.

Temperature range: -50°C to +150°C in a 20°C ambient.

Applications: Conveying hot or cold air, fumes and light dust at low pressure.

Features: Lightweight, very flexible.

Options

- Various lengths upto 4 metres.
- Wire free cuffed ends.
- P4150L 2 ply

Inside Diameter mm	Weight Kg/m	Bend Radius mm	Max. Work. Press. Bar	Max Vacuum Bar
25	0.12	12	1.40	0.50
38	0.16	19	1.40	0.45
51	0.25	25	1.20	0.40
63	0.30	31	1.10	0.35
76	0.41	38	1.00	0.30
83	0.47	41	1.00	0.30
89	0.49	44	0.90	0.25
102	0.57	51	0.90	0.25
127	0.80	63	0.80	0.17
152	1.05	76	0.60	0.14
160	1.09	80	0.60	0.12
178	1.21	89	0.60	0.10
203	1.38	100	0.50	0.07
254	1.65	127	0.40	0.05
305	2.00	152	0.10	0.03