

Layflat Fire Hose

Professional Fire Fighters' Hose



It is constructed with an all synthetic woven textile reinforcement encased in high tensile PVC / Nitrile rubber forming a unified lining and cover. NOVA exceeds the requirements of BS 6391 for type 3 fire hose and is M.E.D. (Ships Wheel) approved for marine use (previously M.C.A).

It also has a Lloyds Registered approval.

Nova's construction and unique PVC / Nitrile rubber blend provide excellent resistance to a wide range of chemicals and oil.

Nova has excellent heat resistance against accidental contact with hot embers.

Nova's strong PVC Nitrile cover provides a tough external coat ensuring excellent abrasion resistance.

No drying is required and cleaning is quick and easy.

Nova has excellent ozone and weather resistance and is suitable for the most demanding environmental conditions.

Inside Diameter.	Coil Diameter (25mtr coil)	Max Working Pressure.	Short Length Burst Pressure.	Weight Kg/Mtr
25mm	35cm	30bar	60bar	.210kg/m
38mm	38cm	25bar	50bar	.230kg/m
45mm	39cm	25bar	50bar	.280kg/m
52mm	41cm	25bar	50bar	.360kg/m
64mm	43cm	25bar	50bar	.500kg/m
70mm	44cm	22bar	45bar	.580kg/m
75mm	46cm	22bar	45bar	.640kg/m
100mm	50cm	17bar	45bar	1.05kg/m

Also available is a complete range of advanced operational fire fighting equipment. Including instantaneous fittings, fire nozzles, fire hose reels and accessories.