

Steam Hose



Super-heated Steam Hose manufactured to BS 5342 Type 2A

Cover: Red EPDM, excellent resistance to ageing & weathering. * = Available in Black Cover.

Branding: TT BS5342 2A year 17 bar - 250 psi size 232°C - 450F

Drain after use

Reinforcement: Spiral wire plies.

Tube: Black EPDM compounded to withstand steam up to 232°C.

Temperature: From -40°C to +232°C

Safety Factor: 10:1 Minimum

Hose I.D.	Hose O.D.	Working Pressure.	Burst Pressure	Weight
13mm	25mm	17bar	170bar	0.50 Kg/Mtr
19mm*	31mm	17bar	170bar	0.75 Kg/Mtr
25mm*	37mm	17bar	170bar	1.00 Kg/Mtr
32mm	46mm	17bar	170bar	1.30 Kg/Mtr
38mm	52mm	17bar	170bar	1.80 Kg/Mtr
51mm	66mm	17bar	170bar	2.30 Kg/Mtr
63mm*	81mm	17bar	170bar	3.30 Kg/Mtr
76mm*	96mm	17bar	170bar	4.50 Kg/Mtr
102mm	124mm	17bar	170bar	5.70 Kg/Mtr

It is strongly recommended that steam hose couplings and the correct size clamps are always used. It is not recommended that couplings are swaged onto steam hose.